according to Regulation (EC) No. 1907/2006



Capadur F7-LangzeitLasur Farblos

Version Revision Date: Print Date Date of last issue: 10.12.2019
1.1 08.12.2020 Date of first issue: 10.12.2019

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : Capadur F7-LangzeitLasur Farblos

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub- : Solvent-borne coatings

stance/Mixture

Recommended restrictions

on use

: within adequate application - none

1.3 Details of the supplier of the safety data sheet

Company : Caparol Farben Lacke GmbH

Roßdörfer Straße 50 64372 Ober-Ramstadt

Telephone : +496154710
Telefax : +4961547170222
E-mail address Responsi- : msds@dr-rmi.com

ble/issuing person

1.4 Emergency telephone number

Emergency telephone num: +49613284463 GBK GmbH

ber 1

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 3 H226: Flammable liquid and vapour.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :

Signal word : Warning

Hazard statements : H226 Flammable liquid and vapour.

according to Regulation (EC) No. 1907/2006



Capadur F7-LangzeitLasur Farblos

Version Revision Date: Print Date Date of last issue: 10.12.2019
1.1 08.12.2020 22.12.2020 Date of first issue: 10.12.2019

Supplemental Hazard : EUH066 Repeated exposure may cause skin

Statements dryness or cracking.

Precautionary statements : P101 If medical advice is needed, have product container or

i label at hand.

P102 Keep out of reach of children.

Prevention:

P210 Keep away from heat, hot surfaces, sparks, open

flames and other ignition sources. No smoking.

P271 Use only outdoors or in a well-ventilated area.

Response:

P303 + P361 + P353 IF ON SKIN (or hair): Take off immedi-

ately all contaminated clothing. Rinse skin with water.

Additional Labelling

EUH208 Contains bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate. May produce an al-

lergic reaction.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : Alkyd-resin-based wood varnish, solvent-containing

Components

Chemical name	CAS-No.	Classification	Concentration
	EC-No.		(% w/w)
	Index-No.		
	Registration number		
Naphtha (petroleum), hydrotreat-	64742-48-9	Asp. Tox. 1; H304	>= 20 - < 30
ed heavy; Low boiling point ydro-	265-150-3		
gen treated naphtha	649-327-00-6		
	01-2119457273-39,		
	01-2119463258-33,		
	01-2119486659-16		
Naphtha (petroleum), hydrotreat-	64742-48-9	Flam. Liq. 3; H226	>= 10 - < 20
ed heavy; Low boiling point ydro-	265-150-3	STOT SE 3; H336	
gen treated naphtha	649-327-00-6	Asp. Tox. 1; H304	
	01-2119457273-39,		
	01-2119463258-33		

according to Regulation (EC) No. 1907/2006



Capadur F7-LangzeitLasur Farblos

Version Revision Date: Print Date Date of last issue: 10.12.2019
1.1 08.12.2020 22.12.2020 Date of first issue: 10.12.2019

bis(1,2,2,6,6-pentamethyl-4- piperidyl) sebacate	41556-26-7 255-437-1 01-2119491304-40	Skin Sens. 1; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410	>= 0,1 - < 0,25
Substances with a workplace exp	osure limit :		
silicon dioxide	7631-86-9		>= 1 - < 10
	231-545-4		
	01-2119379499-16,		
	01-2120105300-82		

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : Never give anything by mouth to an unconscious person.

If you feel unwell, seek medical advice (show the label where

possible).

Move out of dangerous area. First aider needs to protect himself.

If inhaled : Call a physician.

If breathing is irregular or stopped, administer artificial respira-

tion.

If unconscious, place in recovery position and seek medical

advice.

If symptoms persist, call a physician.

Move to fresh air.

In case of skin contact : Do NOT use solvents or thinners.

In case of contact, immediately flush skin with soap and plenty

of water.

Take off all contaminated clothing immediately.

In case of eye contact : If eye irritation persists: Get medical advice/ attention.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue

rinsing.

If swallowed : Seek medical advice.

Clean mouth with water and drink afterwards plenty of water.

If swallowed, DO NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

None known.

according to Regulation (EC) No. 1907/2006



Capadur F7-LangzeitLasur Farblos

Version Revision Date: Print Date Date of last issue: 10.12.2019
1.1 08.12.2020 22.12.2020 Date of first issue: 10.12.2019

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : No information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment.

Use water spray, alcohol-resistant foam, dry chemical or car-

bon dioxide.

Unsuitable extinguishing

media

None known.

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-

fighting

Cool closed containers exposed to fire with water spray. In case of fire hazardous decomposition products may be

produced such as:

Carbon monoxide, carbon dioxide and unburned hydrocar-

bons (smoke).

5.3 Advice for firefighters

Special protective equipment :

for firefighters

In the event of fire, wear self-contained breathing apparatus.

Further information : Standard procedure for chemical fires.

In the event of fire and/or explosion do not breathe fumes.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Do not get in eyes, on skin, or on clothing.

When workers are facing concentrations above the exposure

limit they must use appropriate certified respirators.

Ensure adequate ventilation. Remove all sources of ignition.

6.2 Environmental precautions

Environmental precautions : Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Do not flush into surface water or sanitary sewer system.

according to Regulation (EC) No. 1907/2006



Capadur F7-LangzeitLasur Farblos

Version Date of last issue: 10.12.2019 Revision Date: **Print Date** 1.1 22.12.2020 Date of first issue: 10.12.2019 08.12.2020

6.3 Methods and material for containment and cleaning up

Keep in suitable, closed containers for disposal. Methods for cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

6.4 Reference to other sections

For further information see Section 7 of the safety data sheet.

For personal protection see section 8., For disposal considerations see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling Non-sparking tools should be used.

For personal protection see section 8.

Avoid exceeding the given occupational exposure limits (see

section 8).

Provide sufficient air exchange and/or exhaust in work rooms.

In addition, the current technical information for this product and its application on www.caparol.com must be observed.

Advice on protection against

fire and explosion

Vapours may form explosive mixtures with air. Vapours are heavier than air and may spread along floors. Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

Avoid contact with the skin and the eyes. Wash hands before Hygiene measures

eating, drinking, or smoking. Do not eat, drink or smoke when

using this product.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

Store in original container. Store between 5 and 25 °C in a dry, well ventilated place away from sources of heat, ignition and direct sunlight. Containers which are opened must be

carefully resealed and kept upright to prevent leakage.

Storage class (TRGS 510) 3, Flammable liquids

7.3 Specific end use(s)

Specific use(s) : This information is not available.

according to Regulation (EC) No. 1907/2006



Capadur F7-LangzeitLasur Farblos

Version Revision Date: Print Date Date of last issue: 10.12.2019
1.1 08.12.2020 22.12.2020 Date of first issue: 10.12.2019

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis	
Naphtha (petrole- um), hydrotreated heavy; Low boiling point ydrogen treated naphtha	64742-48-9	AGW	300 mg/m3	DE TRGS 900	
	Peak-limit: excursion factor (category): 2;(II)				
	Further information: See also No. 2.9 of the TRGS 900, Commission for dan-				
	gerous substances, Group exposure limit for hydrocarbon solvent mixtures				
Naphtha (petrole- um), hydrotreated heavy; Low boiling	64742-48-9	AGW	300 mg/m3	DE TRGS 900	
point ydrogen					
treated naphtha	5) 0 (!!)		
	Peak-limit: excursion factor (category): 2;(II)				
	Further information: See also No. 2.9 of the TRGS 900, Commission for dangerous substances, Group exposure limit for hydrocarbon solvent mixtures				
silicon dioxide	7631-86-9	TWA (Respirable dust)	0,1 mg/m3	2004/37/EC	
	Further information: Carcinogens or mutagens				
		AGW (Inhalable	4 mg/m3	DE TRGS	
		fraction)	(Silica)	900	
	Further information: When there is compliance with the OEL and biological				
	tolerance values, there is no risk of harming the unborn child, Colloidal amor-				
	phous silica, including pyrogenic silica and in wet processes manufactured				
	silica (precipitated silica, silicagel)., Senate commission for the review of com-				
	pounds at the work place dangerous for the health (MAK-commission).				

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health ef-	Value
			fects	
Silicic acid, aluminum	Workers	Inhalation	Long-term local ef-	4,00 mg/m3
sodium salt			fects	

8.2 Exposure controls

Personal protective equipment

Eye protection : German trade association rules - BGR 192 Eye protection

Goggles

Hand protection

Material : Nitrile rubber

according to Regulation (EC) No. 1907/2006



Capadur F7-LangzeitLasur Farblos

Version Revision Date: Print Date Date of last issue: 10.12.2019
1.1 08.12.2020 22.12.2020 Date of first issue: 10.12.2019

Glove thickness : 0,2 mm Protective index : Class 3

Remarks : Gloves should be discarded and replaced if there is any indi-

cation of degradation or chemical breakthrough. Before removing gloves clean them with soap and water. Wear suita-

ble gloves tested to EN374.

German trade association leaflet: Carry gloves (ZH 1/706)

Skin and body protection : Safety shoes

Long sleeved clothing

Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Skin should be washed after contact.

During spray application: impervious clothing

Respiratory protection : Roller application or brushing: This product should not be

used under conditions of poor ventilation unless a protective mask with an appropriate gas filter (i.e. type A1 according to

standard EN 14387) is used.

German trade association rules - BGR 190 Breathing protec-

tion

During spray application: Do not breathe spray dust. Use

A2/P2 combination filter for paint spraying.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance : liquid

Colour : No data available

Odour : No data available

Odour Threshold : Not relevant

pH : 6,95

Concentration: 10 %

Melting point/freezing point : not determined

Boiling point/boiling range : not determined

according to Regulation (EC) No. 1907/2006



Capadur F7-LangzeitLasur Farblos

Version Revision Date: Print Date Date of last issue: 10.12.2019
1.1 08.12.2020 22.12.2020 Date of first issue: 10.12.2019

Flash point : 48,5 °C

Evaporation rate : Not applicable

Upper explosion limit / Upper

flammability limit

not determined

Lower explosion limit / Lower :

flammability limit

not determined

Vapour pressure : not determined

Relative vapour density : not determined

Relative density : not determined

Density : 0,9500 g/cm3

Solubility(ies)

Water solubility : insoluble

Partition coefficient: n-

octanol/water

not determined

Auto-ignition temperature : not determined

Decomposition temperature : Not applicable

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : > 20,5 mm2/s (40 °C)

Flow time : > 60 s at 23 °C

Cross section: 6 mm Method: ISO 2431

Explosive properties : Not applicable

Oxidizing properties : Not applicable

9.2 Other information

Flammability (liquids) : Sustains combustion

according to Regulation (EC) No. 1907/2006



Capadur F7-LangzeitLasur Farblos

Version Revision Date: Print Date Date of last issue: 10.12.2019
1.1 08.12.2020 22.12.2020 Date of first issue: 10.12.2019

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : Vapours may form explosive mixture with air.

Hazardous decomposition products formed under fire condi-

tions.

10.4 Conditions to avoid

Conditions to avoid : Protect from frost, heat and sunlight.

10.5 Incompatible materials

Materials to avoid : Incompatible with acids and bases.

Incompatible with oxidizing agents.

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Product:

Acute oral toxicity : Remarks: Based on available data, the classification criteria

are not met.

Acute inhalation toxicity : Remarks: Based on available data, the classification criteria

are not met.

Acute dermal toxicity : Remarks: Based on available data, the classification criteria

are not met.

Components:

silicon dioxide:

Acute oral toxicity : LD50 Oral (Rat): 10.000 mg/kg

according to Regulation (EC) No. 1907/2006



Capadur F7-LangzeitLasur Farblos

Version **Revision Date:** Print Date Date of last issue: 10.12.2019 1.1 08.12.2020 22.12.2020 Date of first issue: 10.12.2019

Skin corrosion/irritation

Product:

Remarks May cause skin irritation in susceptible persons.

Serious eye damage/eye irritation

Product:

Remarks According to the classification criteria of the European Union,

the product is not considered as being an eye irritant.

Respiratory or skin sensitisation

Product:

Remarks Repeated contact may cause allergic reactions in very sus-

ceptible persons.

SECTION 12: Ecological information

12.1 Toxicity

Product:

Remarks: No data available Toxicity to fish

Toxicity to daphnia and other : Remarks: No data available

aquatic invertebrates

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment This substance/mixture contains no components considered

> to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher...

12.6 Other adverse effects

Product:

according to Regulation (EC) No. 1907/2006



Capadur F7-LangzeitLasur Farblos

Version Revision Date: Print Date Date of last issue: 10.12.2019
1.1 08.12.2020 22.12.2020 Date of first issue: 10.12.2019

Additional ecological infor-

mation

An environmental hazard cannot be excluded in the event of

unprofessional handling or disposal.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product :

Waste should not be disposed of via wastewater.

Contaminated packaging : Only completely emptied containers should be given for recy-

cling.

Waste Code : used product

080112, waste paint and varnish other than those mentioned

in 08 01 11*

SECTION 14: Transport information

14.1 UN number

ADN : UN 1263
ADR : UN 1263
RID : UN 1263
IMDG : UN 1263
IATA : UN 1263

14.2 UN proper shipping name

ADN : PAINT
ADR : PAINT
RID : PAINT
IMDG : PAINT
IATA : Paint

14.3 Transport hazard class(es)

ADN : 3
ADR : 3
RID : 3
IMDG : 3
IATA : 3

according to Regulation (EC) No. 1907/2006



Capadur F7-LangzeitLasur Farblos

Version **Revision Date:** Print Date Date of last issue: 10.12.2019 1.1 08.12.2020 22.12.2020 Date of first issue: 10.12.2019

14.4 Packing group

ADN

Packing group Ш Classification Code F1 Hazard Identification Number : 30 Labels

ADR

Packing group Ш Classification Code F1 Hazard Identification Number : 30 Labels 3 Tunnel restriction code (D/E)

Packing group Ш Classification Code F1 Hazard Identification Number : 30 Labels 3

IMDG

Packing group Ш Labels 3 EmS Code F-E, <u>S-E</u>

IATA (Cargo)

Packing instruction (cargo 366

aircraft)

Y344 Packing instruction (LQ) Packing group Ш

Labels Flammable Liquids

IATA (Passenger)

Packing instruction (passen-355

ger aircraft)

Packing instruction (LQ) Y344 Packing group Ш

Labels Flammable Liquids

14.5 Environmental hazards

Environmentally hazardous no

ADR

Environmentally hazardous no

RID

Environmentally hazardous no

IMDG

Marine pollutant no

14.6 Special precautions for user

according to Regulation (EC) No. 1907/2006



Capadur F7-LangzeitLasur Farblos

Version Revision Date: Print Date Date of last issue: 10.12.2019 1.1 08.12.2020 22.12.2020 Date of first issue: 10.12.2019

Remarks ADR: Packages smaller than or equal to 450 litres, not

goods/merchandise of Class 3

IMDG: Packages smaller than or equal to 450 litres, not

goods/merchandise of Class 3

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII)

Conditions of restriction for the following entries should be considered:

Number on list 3

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59).

This product is a mixture and does not contain Substances of Very High Concern (SVHC) equal or above 0.1%. Therefore no advised uses have to be defined and no chemical safety assessment has to be gener-

ated.

REACH - List of substances subject to authorisation

(Annex XIV)

None

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances. P₅c FLAMMABLE LIQUIDS

34 Petroleum products: (a)

> gasolines and naphthas, (b) kerosenes (including jet fuels), (c) gas oils (including diesel fuels, home heating oils and gas oil blending streams),(d) heavy fuel oils (e) alternative fuels serving the same purposes and with similar properties as regards

according to Regulation (EC) No. 1907/2006



Capadur F7-LangzeitLasur Farblos

Version Revision Date: Print Date Date of last issue: 10.12.2019
1.1 08.12.2020 Date of first issue: 10.12.2019

flammability and environmental hazards as the products referred to in points (a) to (d)

Water contaminating class

(Germany)

1 slightly water endangering

Classification according to AwSV, Annex 1 (5.2)

Product code for laquers and

paints / Giscode

: M-KH02 Solvent-based varnishes/wood glaze, aromatics re-

moved

. : BSL40 Coating materials, strongly solvent-based, aromatic-

free, classified

Volatile organic compounds : Directive 2004/42/EC

< 41 % < 390 g/l

Other regulations:

Take note of Law on the protection of mothers at work, in education and in studies (Maternity Protection Act - MuSchG).

15.2 Chemical safety assessment

A Chemical Safety Assessment is not required for this substance.

SECTION 16: Other information

Full text of H-Statements

H226 : Flammable liquid and vapour.

H304 : May be fatal if swallowed and enters airways.

H317 : May cause an allergic skin reaction. H336 : May cause drowsiness or dizziness.

H400 : Very toxic to aquatic life.

H410 : Very toxic to aquatic life with long lasting effects.

Full text of other abbreviations

Aquatic Acute : Short-term (acute) aquatic hazard
Aquatic Chronic : Long-term (chronic) aquatic hazard

Asp. Tox. : Aspiration hazard Flam. Liq. : Flammable liquids Skin Sens. : Skin sensitisation

STOT SE : Specific target organ toxicity - single exposure

2004/37/EC : Europe. Directive 2004/37/EC on the protection of workers

from the risks related to exposure to carcinogens or mutagens

at work

DE TRGS 900 : Germany. TRGS 900 - Occupational exposure limit values.

2004/37/EC / TWA : Long term exposure limit

according to Regulation (EC) No. 1907/2006



Capadur F7-LangzeitLasur Farblos

Version Revision Date: Print Date Date of last issue: 10.12.2019
1.1 08.12.2020 22.12.2020 Date of first issue: 10.12.2019

DE TRGS 900 / AGW : Time Weighted Average

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Constitution and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemicals Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; IECSC - Inventory of Existing Chemicals Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELSR - No Observed (Adverse) Effect Level; Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELSR - No Observed (Adverse) Effect Level; NOELSR - No Observed (Adverse) Effect Leve

Further information

Other information:

No exposure scenario communication is required for this product according to REACH Regulation No. 1907/2006 EC.

Communication of Uses is not required in accordance with REACH Article 31(1)(a) - registered substances / mixtures do not meet the criteria for classification as hazardous in accordance with Regulations 1272/2008 EC or 1999/45/EC.

Sources of key data used to compile the Safety Data Sheet:

ECHA WebSite

ACGIH (American Conference of Government Industrial Hygienists). 2014 TLVs and BEIs. Threshold Limit Values (TLVs) for chemical substances and physical agents and Biological Exposure Indices (BEIs) with Seventh Edition documentation. 2014 ACGIH, Cincinnati OH

NIOSH - Registry of toxic effects of chemical substances

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities

SAX'S - Dangerous properties of industrial materials

GESTIS - Database on hazardous substances - Institut für Arbeitsschutz der Deutschen Gesetzlichen Unfallversicherung (IFA, Institute for Occupational Safety and Health of the German Social Accident Insurance)

Toxnet - Toxicology Data Network

Classification of the mixture:

Classification procedure:

Flam. Liq. 3 H226 Based on product data or assessment

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific

according to Regulation (EC) No. 1907/2006



Capadur F7-LangzeitLasur Farblos

Version Revision Date: Print Date Date of last issue: 10.12.2019
1.1 08.12.2020 Date of first issue: 10.12.2019

material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

REACH Information

According to our legal obligation we implement the Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH). We will adjust and update our safety data sheets on a regular base in accordance with the information of our upstream-suppliers. As usual we will inform you about the adjustments.

Regarding to the REACH regulation we would like to point out that DAW as a downstream user will not register on behalf of our company. We will rely on information from our suppliers. As soon as new information is available our safety data sheets will be amended accordingly.

DE / EN