

Capatect-Thermoschiene 6680/55

Wall attachment for ETICS between perimeter insulation and facade

Product Description

Field of Application	PVC angle with 40 mm vertical side length with round and oblong holes for fixing; 55 mm horizontal side length. Bottom base for thermal insulation boards. To be used as well in combination with Capatect Thermoprofil 6680/30 (with front side drip edge).
Function	Wall side fixing profile with low thermal conductivity to avoid thermal bridges.
Material Properties	Stable plastic profile, side thickness ~ 2 mm; angle ~ 90° Also available in side length 100 mm and 160 mm
Packaging/Package Size	Bar length 200 cm; Carton containing 10 units = 20 m
Colours	White
Storage	on a planar surface, tension-free . Protect from direct sunlight, heating and from mechanical loads.
Supplementary Product	Capatect-Thermoprofil 6680/30
Product No.	6680/55

Sales programme

Capatect-Thermoschiene		
Product-N°	Horizontal side length [mm]	For insulation board thickness [mm]
6680/55	55	60 to 100
6680/100	100	100 to 150
6680/160	160	160 to 200
Complement profile: Capatect Thermoprofil		
6680/30	74	---



Application

Substrate Preparation

Remove projecting mortar burrs and fill cavities in render/plaster.

Consumption

per meter: 1.0 m

Application Conditions

Processing temperature: > +5 °C for product, substrate and ambient air.

Installation

Mark setting line by a chalk line.

Install the Capatect-Thermoschiene flush and tension-free to the surface with Capatect-Montage-Schlagschrauben (knock-in anchors); max. anchor distance 30 cm.

Fix subsequent profil with 3 mm gap. Align substrate irregularities with adequate Capatect spacer bevor final knock-in of the anchors.

Advice

Disposal

Dispose remnants as per EWC 170904 (mixed construction and demolition waste)